




# ImaSight 4600 DR Veterinary System



Digital Clarity and  
Dedicated Client Care.  
A System for Today...  
And Tomorrow.

**Capture.** Get digital radiography images using your conventional x-ray equipment and procedures.

**Visualize.** The Imasight Sensor represents advanced CCD technology incorporating 16 million pixels delivering a high-dynamic range image. This means more information in crystal-clear razor sharp images for your diagnostic practice.

**Say goodbye to film.**

ImaSight Vision: Your Human  
Interface Software

**Touch.** At your fingertips, share, manipulate and analyze your images via a touchscreen interface.

**Ease of Use.** View, annotate, save your images with a simple, full-featured, intuitive user interface software.

**Your Data is Safe.** With the touch of a finger, backup your data for peace of mind.

**Enhance.** Deliver better patient care, while increasing throughput and productivity with a conversion to an Imasight DR System.

**Simplify.** Simplify your workflow, obtain a higher level of efficiency in no time. You can even get rid of film drawers.

**Save time.** Superior images from the Imasight 4600 arrive in seconds permitting immediate visibility and faster diagnosis.

**Easy integration into your existing system.**

**Go Green.**



**No Chemicals.** Digital radiography doesn't require chemicals for capturing images.

**No Odours.** Better ambiance at your clinic.

**No Disposal.** Protecting the environment.

IMASIGHT



Your Practice.  
Our Focus.

# ImaSight 4600 DR System Specifications



## Retrofit Sensor System

### Sensor

- Direct to Digital
- Image acquisition time: 7 - 15 seconds
- Target area: 14" x 17" / 35.56cm x 43.18cm
- Resolution: 4.6 lp/mm / Pixel pitch: 108um
- ADC 16 bits [DICOM compatible image]
- Maintenance free

### Acquisition Workstation

- Dell OPTI 360 Core Duo 2.7GHz / 2GB Ram
- Windows XP SP3 operating system
- 320 GB hard drive
- External backup drive - 500 GB

### High-Resolution Monitor

- Touchscreen
- 20" viewable area
- 2.0 megapixels [1600 x 1200 LCD]

### Cables / Power Supply

- Ethernet cables (15'/4.57m + 3'/0.91m) + Ethernet isolator
- DB-9 serial cable (15'/4.57m)
- Ethernet network cable (14'/4.26m)
- 6 input surge suppressor power strip

### ImaSight Vision Software

- One (1) Vision Capture Station license
- One (1) Vision Diagnostic Station license
- Includes a two (2) year subscription for all software updates and releases, toll-free telephone and remote online software support
- Additional ImASight Vision software licenses are available

### Warranty

- Five (5) years on sensor
- Two (2) years on parts
- Other components, such as computer, monitor, and related equipment carry manufacturers' warranties

## X-Ray System Specifications [Turnkey]

### X-Ray Generator

- Power: 30kW
- kVp Range: 40 - 125kV
- mAs Range: 0.1 - 500 mAs
- mA Range: 10 - 400mA
- Membrane console
- Anatomical programming
- Power supply cabinet: 27" x 14" x 45"

### X-Ray Tube

- 0.6 / 1.5 focal spots
- 200,000 Hu

### Table

- Fixed 40 inch SID tube stand
- Manual collimator
- 5 foot (152cm) table top
- Four-way floating table top
- Exposure foot pedal
- High voltage cables (15 feet / 4.57 metres)

### Warranty

- Five (5) years on x-ray system
- One (1) year on x-ray tube

## Our Promise

**Reliability.** The ImASight 4600H DR Sensor contains no moving parts and is maintenance free. We deliver great consistent images over years of use.

**Robust.** Built to last, our sensor requires no special cooling and has no electronics exposed to x-rays.

**Service & Support.** North American based support for your convenience. We use remote diagnostics to quickly assist you and expedite service.

## ImaSight Inc.

Suite 10, 925 Boulevard de la Carrière  
Gatineau, QC, J8Y 6W5 CANADA

+1 [819] 777-7979  
+1 [613] 822-5195

Sales inquiries: +1 [888] 707-4041  
sales@imasight.com



IMASIGHT